

Più CUBE 13

Power raised to the cube degree!

Più CUBE

Top of the range: maximum power, great efficiency.
Qualities raised to the cube degree for a portable that can deliver up to 400 m³/h of fresh air.
Maximum comfort for large rooms.



Functions

Più features all the desirable functions:

- 1- Ventilation to use the conditioner as a simple fan
- 2- Dehumidification to cool, with an emphasis on lowering the humidity of the surroundings
- 3- Cooling
- 4- Automatic mode which modulates the functioning of the conditioner according to where it is placed, and also regulates its power to bring it to a condition considered optimum in terms of ventilation, dehumidification and temperature
- 5- Timer which automatically switches on and off the machine.

Design

A Dario Tanfoglio design Più Cube has a wonderful silver color casing that enriched the essential shape giving to it a touch of refinement and value.



Remote Control

All of these functions together with the possibility of modifying the ventilation rate, and setting its automatic operation as well as setting the on/off timer, are easily activated from the practical remote.

All the options set are also easily visible on the LCD displays of both the machine and the remote.

Cod. 01066

Maximum Cooling capacity (35°C/80% UR)	BTU/h	13000
Cooling capacity (1)	kW	3,3
Power absorption in cooling mode (1)	W	1100
Yearly energy consumption in cooling mode (1)	kWh	550
E.E.R.	—	3,00
Energy Efficiency Class in cooling mode (1)	—	A
Power supply	V-F-Hz	230-1-50
Dehumidification capacity	l/h	1,2
Room air flow (max/min)	m ³ /h	400/255
Fan speeds	—	3
Flexible pipe (lenght x diameter)	mm	1500x120
Maximun remote control range (distance / angle)	m/°	8/80
Dimensions (W x H x D)	mm	460x760x395
Weight (without packing)	Kg	30
Sound level	db(A) min-max	38-48
Refrigerant gas / charge	Tipo/Kg	R410A/0,48
Maximum operating pressure	MPa	3,60

OPERATIONAL LIMITS

	Indoor temperature	Outdoor temperature
Maximum operating temperature in cooling mode	DB 35°C - WB 32°C	DB 43°C - WB 32°C
Minimum operating temperature in cooling mode	DB 16°C	DB 18°C - WB 16°C

(1) The technical data are referred to EN 14511.